

Single Fiber Transceiver 2 Digital Video, 2 Bi-directional RS232 Data & 1 Bi-directional Audio

FEATURES:

- Compatible with NTSC; RS-170A, RS-343A and PAL
- Real-time 8-bit video
- Diagnostics: Video, Data, Power & Optical Presence
- High Speed, Full Duplex Data
- Line Level Audio Interface

SPECIFICATIONS:

Video:(2)

I/O Level 1Vp-p
 I/O Impedance 75 Ω
 Bandwidth 7 MHz
 Differential Gain 2%
 Differential Phase 0.7°
 SNR 60 dB
 Connector BNC

Data:(2)

Interface RS-232,
 Format Asynchronous
 Rate DC to 100 Kb/s
 Connector Terminal Block

Audio:

I/O Level (balanced) 0 dBm
 Impedance 600 ohms
 Bandwidth 20 Hz to 10 KHz
 THD @ 1 KHz 1%
 SNR 75 dB
 Connector Terminal Block

Optical:

Wavelength 1300/1550 nm
 Loss Budget (62.5/125 μm) 12 dB
 Distance (limited by fiber dispersion) 2 km
 Connector ST

Temperature (Operating)

-40°C to +75°C, non-condensing

Power Supply:

Module - 12 VDC AFI PS-12D+
 Rack Card - AFI SR 20/2

Size:

Module - 8 1/8" x 4 1/8" x 1 5/8"
 Rack Card (2 rack slots) 6 1/2" x 2" x 5"



The American Fibertek 92P338 Series transmits 2 high-quality, state of the art, 8-bit digital video, with 2 bi-directional RS232 data channels and 1 bi-directional audio channel on one multimode optical fiber.

Designed to be completely transparent, this system requires no field adjustments at installation or additional maintenance thereafter. Diagnostic indicators provide a quick visual indication of system status.

Equipment may be ordered as stand alone modules or rack cards that are mounted in the American Fibertek Card Cages: SR-20R/1 or SR20/2.

Product Ordering Information:

- | | |
|-----------|-----------------------|
| MT-92P338 | Module Transmitter |
| MR-92P338 | Module Receiver |
| RT-92P338 | Rack Card Transmitter |
| RR-92P338 | Rack Card Receiver |

