



**46-PoE+
SERIES
MULTIMODE**

10/100 Base-T to 100 Base-FX Ethernet Media Converter / 3 Port Switch with PoE+

FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Singlemode and Multimode Fiber Versions Available
- ◆ Power Over Ethernet on Both Ports

SPECIFICATIONS:

Ethernet:

Data Rate

- Auto negotiated 10/100 Mb/s
- ConnectorRJ45
- PoE (2 RJ45 ports)..... 802.3af
- PoE (2 RJ45 ports)..... 802.3at

Optical:

- One Fiber..... 1310/1550 nm
- Two Fiber..... 1310 nm
- Source:
 - Multimode Two Fiber LED
 - Multimode One Fiber..... Laser
- Distance
 - FX 62/125u 2 km
- Loss Budget11 dB
- Connector SC,ST

Power:

- Voltage 48 VDC
- Current..... 200 mA
- Connector2 Pin Terminal Block

Power Supply:

Module: 48VDC @ 60W
AFI Part #: PS-48V-60W-1
(Sold separately)

Environmental:

- Temperature.....-40 °C to +75 °C
- Humidity.....5 % to 95 %

Size:

Module..... 4 1/4" x 4 1/4" x 1 1/8"

9/26/12JPM



The American Fibertek 46-PoE+ Series transmits and receives (2) copper 10/100 Base-T Ethernet signals at the RJ45 ports and (1) optical 100 Base-FX over 1 or 2 multimode fibers. The system is comprised of two units forming a point-to-point communications link.

The 46-PoE+Series sources power to devices from the RJ45 ports over the copper connection. Both RJ45 ports may be used to deliver 802.3af (15 watts) or 802.3at (30 watts) to PD powered devices. An external PS-48V-60W-1 power supply is required.

The system is designed to be completely transparent with auto negotiation features which automatically configures the unit for the correct speed (10/100 Base-T).

Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

ORDERING INFORMATION:

- MTX-46-FX-SC-PoE+ One Fiber Module Transmitter FX Multimode SC Connector
- MTX-46-FX-ST-PoE+ One Fiber Module Transmitter FX Multimode ST Connector
- MX-46-FX-SC-PoE+ Two Fiber Module FX Multimode SC Connector
- MX-46-FX-ST-PoE+ Two Fiber Module FX Multimode ST Connector

PS-48V-60W-1 48 Volt 60 Watt Power Supply

The PoE module is typically used only at the system edge (to power the camera etc.). The mating unit would then be the non PoE version of the product which is available in module or rack card packages.