



**46-PoE-HP
SERIES
MULTIMODE**

10/100 Base-T to 100 Base-FX Ethernet Media Converter / 3 Port Switch with 60W PoE

“Approved for AXIS Q6032-E PTZ Dome Network Camera”

FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Auto Negotiate 10/100 Ports
- ◆ Auto MDI/MDIX Detection
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Singlemode Fiber Versions Available
- ◆ Power (60 Watts) Over Ethernet on 1 Port
- ◆ Two RJ45 Data Ports Available
- ◆ Extended Temperature Range

SPECIFICATIONS:

Ethernet:

Data Rate
Auto negotiated 10/100 Mb/s
Connector RJ45
PoE (1 port)60 Watts

Optical:

One Fiber..... 1310/1550 nm
Two Fiber..... 1310 nm
Source:
Multimode Two FiberLED
Multimode One Fiber.....Laser
Distance
FX 62/125u 2 km
Loss Budget 11 dB
Connector SC, ST

Power:

Voltage..... 48 VDC
Current..... 200 mA
Connector2 Pin Terminal Block

Power Supply:

Module: 48VDC @ 60W
AFI Part #: PS-48V-60W-1
(Sold separately)

Environmental:

Temperature -40 °C to +65 °C
Humidity 5 % to 95 %

Size:

Module 4.3" x 4.3" x 1.2"
Power Supply..... 4.6" x 3.6" x 1.6"
9/26/12JPM



The American Fibertek 46-PoE-HP Series transmits and receives (2) copper 10/100 Base-T Ethernet signals at the RJ45 ports and (1) optical 100 Base-FX over 1 or 2 multimode fibers. The system is comprised of two units forming a point-to-point communications link.

The 46-PoE-HP Series also sources up to 60 Watts of power to an Ethernet powered device (PD) from one RJ45 port. The power is carried over all 4 pairs of the Ethernet cable. However, it is required that the PD have independent discovery and classification interfaces for both the data pair and the spare pair of the Ethernet cable.

Both RJ45 ports may be used to deliver Ethernet data to devices. An external PS-48V-60W-1 power supply is required.

The system is designed to be completely transparent with auto negotiation features which automatically configures the unit for the correct speed (10/100 Base-T).

Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

ORDERING INFORMATION:

- MTX-46-FX-SC-PoE-HP One Fiber Module Transmitter FX Multimode SC Connector
- MTX-46-FX-ST-PoE-HP One Fiber Module Transmitter FX Multimode ST Connector
- MX-46-FX-SC-PoE-HP Two Fiber Module FX Multimode SC Connector
- MX-46-FX-ST-PoE-HP Two Fiber Module FX Multimode ST Connector

PS-48V-60W-1 48 Volt 60 Watt Power Supply

The PoE module is typically used only at the system edge (to power the camera etc.). The mating unit would then be the non PoE version of the product which is available in module or rack card packages. See Series 46 datasheet.