

10/100/1000Base-T to 1000 Base-ZX Ethernet Media Converter / 3 Port Switch with PoE

FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100/1000 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Singlemode and Multimode Fiber Versions Available
- ◆ Power Over Ethernet on Both Ports

SPECIFICATIONS:

Ethernet:

Data Rate

Auto negotiated ... 10/100/1000 Mb/s

ConnectorRJ45

PoE (2 RJ45 ports)..... 802.3af

PoE (1 RJ45 port)..... 802.3at

Optical:

One Fiber..... 1490/1550 nm

Two Fiber.....1550nm

Distance

ZX 9/125u 70 km

Loss Budget24 dB

ConnectorSC

Power:

Voltage 48 VDC

Current..... 200 mA

Connector2 Pin Terminal Block

Power Supply:

Module: 48VDC @ 60W

AFI Part #: PS-48V-60W

(Sold separately)

Environmental:

Temperature-40 °C to +75 °C

Humidity.....5 % to 95 %

Size:

Module.....4¼" x 4¼" x 1⅛"



The American Fibertek 48-ZX Series transmits and receives (2) copper 10/100/1000Base-T Ethernet signals at the RJ45 ports and (1) optical 1000 Base-ZX over 1 or 2 singlemode fibers up to a distance of 70 km. The system is comprised of two units forming a communications link.

The Series 48-ZX Series sources power to devices from the RJ45 ports over the copper connection. Both RJ45 ports may be used to deliver low power 802.3af (15 watts) to devices. A single RJ45 port is used to deliver high power 802.3at (30 watts) to a single device. An external PS-48V-60W power supply is required for the PoE module.

The system is designed to be completely transparent with auto negotiation features which automatically configures the unit for the correct speed (10/100/1000 Base-T).

Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

ORDERING INFORMATION:

MTX-48-ZX-SL-SC-PoE One Fiber Module Transmitter LX Singlemode SC Connector

MTX-48-ZX-SL-ST-PoE One Fiber Module Transmitter LX Singlemode ST Connector

MX-48-ZX-SL-SC-PoE Two Fiber Module LX Singlemode SC Connector

MX-48-ZX-SL-ST-PoE Two Fiber Module LX Singlemode ST Connector

PS-48V-60W

48 Volt 60 Watt Power Supply

The PoE module is typically used only at the system edge (to power the camera etc.). The mating unit would then be the non PoE version of the product which is available in module or rack card packages.

9/26/12JPM