



**49-ZX-PoE
SERIES
SINGLEMODE**

**(2) 10/100/1000Base-T & (2) 1000Base-ZX Ethernet
4 Port Switch / Drop & Repeat Transceiver with PoE**

FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Drop and Repeat Capability
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100/1000 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Singlemode and Multimode Fiber Versions Available

SPECIFICATIONS:

Ethernet:

Data Rate
Auto negotiated..... 10/100/1000 Mb/s
Connector RJ45
PoE (2 RJ45 ports) 802.3af
PoE (1 RJ45 port) 802.3at

Optical:

One Fiber..... 1490/1550 nm
Two Fiber..... 1550nm
Distance
ZX 9/125u..... 70 km
Loss Budget24 dB
ConnectorSC

Power:

Voltage..... 48 VDC
Current..... 200 mA
Connector 2 Pin Terminal Block

Power Supply:

Module: 48VDC @ 60W
AFI Part #: PS-48V-60W
(Sold separately)

Environmental:

Temperature -40 °C to +75 °C
Humidity..... 5 % to 95 %

Size:

Module..... 4¼" x 4¼" x 1⅝"



The American Fibertek 49-ZX Series transmits and receives (2) copper 10/100/1000Base-T Ethernet signals at the RJ45 ports and (1) optical 1000 Base-ZX over 1 or 2 singlemode fibers up to a distance of 70 km. The system is comprised of two units forming a communications link.

The 49-ZX Series also sources power to devices from the RJ45 ports over the copper connection. Both RJ45 ports may be used to deliver low power 802.3af (15 watts) to devices. A single RJ45 port is used to deliver high power 802.3at (30 watts) to a single device. An external PS-48V-60W power supply is required for the PoE module.

The system is designed to be completely transparent with auto negotiation features which automatically configures the unit for the correct speed (10/100/1000 Base-T).

Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

ORDERING INFORMATION:

MX-49-ZX-SL-SC-PoE	Two Fiber/Port, Module LX Multimode SC Connector
MX-49-ZX-SL-1F-SC-PoE	One Fiber/Port, Module LX Multimode SC Connector
MX-49-ZX-SL-ST-PoE	Two Fiber/Port, Module LX Multimode ST Connector
MX-49-ZX-SL-1F-ST-PoE	One Fiber/Port, Module LX Multimode ST Connector

PS-48V-60W 48 Volt 60 Watt Power Supply

The PoE module is typically used only at the system edge (to power the camera etc.). The mating unit would then be the non PoE version of the product which is available in module or rack card packages.

9/26/12JPM