



**48SL-PoE
SERIES
SINGLEMODE**

10/100/1000Base-T to 1000 Base-LX Ethernet Media Converter / 3 Port Switch with PoE

FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100/1000 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Singlemode and Multimode Fiber Versions Available
- ◆ Power Over Ethernet on Both Ports

SPECIFICATIONS:

Ethernet:

Data Rate
Auto negotiated ... 10/100/1000 Mb/s
ConnectorRJ45
PoE (2 RJ45 ports)..... 802.3af
PoE (1 RJ45 port)..... 802.3at

Optical:

One Fiber..... 1310/1550 nm
Two Fiber..... 1310 nm
Source Laser
Distance
LX 9/125u 10 km
Loss Budget10 dB
Connector SC,ST

Power:

Voltage 48 VDC
Current..... 200 mA
Connector2 Pin Terminal Block

Recommended Power Supply:

48VDC @ 30W (Sold separately)

Environmental:

Temperature-40 °C to +75 °C
Humidity.....5 % to 95 %

Size:

Module...4 1/4" x 4 1/4" x 1 1/8"



The American Fibertek 48SL-PoE Series transmits and receives (2) copper 10/100/1000 Base-T Ethernet signals at the RJ45 ports and (1) optical 1000 Base-X over 1 or 2 singlemode fibers. The system is comprised of two units forming a point-to-point communications link.

The Series 48SL-PoE Series sources power to devices from the RJ45 ports over the copper connection. Both RJ45 ports may be used to deliver low power 802.3af (15 watts) to devices. A single RJ45 port is used to deliver high power 802.3at (30 watts) to a single device. An external power supply is required for the PoE module.

The system is designed to be completely transparent with auto negotiation features which automatically configures the unit for the correct speed (10/100/1000 Base-T).

Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

ORDERING INFORMATION:

- MTX-48-LX-SL-SC-PoE One Fiber Module Transmitter LX Singlemode SC Connector
- MTX-48-LX-SL-ST-PoE One Fiber Module Transmitter LX Singlemode ST Connector
- MX-48-LX-SL-SC-PoE Two Fiber Module LX Singlemode SC Connector
- MX-48-LX-SL-ST-PoE Two Fiber Module LX Singlemode ST Connector

POWER SUPPLY:

- PS-48D Universal Input to 48V 30W Output 0 to 50°C
- PS-4830 Universal Input to 48V 30W Output -40 to 75°C

The PoE module is typically used only at the system edge (to power the camera etc.). The mating unit would then be the non PoE version of the product which is available in module or rack card packages.