

## (2) 10/100/1000Base-T & (2) 1000Base-SX/LX Ethernet 4 Port Switch / Drop & Repeat Transceiver with PoE

### FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Drop and Repeat Capability
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100/1000 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Singlemode and Multimode Fiber Versions Available

### SPECIFICATIONS:

#### Ethernet:

Data Rate

Auto negotiated ..... 10/100/1000 Mb/s

Connector ..... RJ45

PoE (2 RJ45 ports) ..... 802.3af

PoE (1 RJ45 port) ..... 802.3at

#### Optical:

One Fiber ..... 1310/1550 nm

Two Fiber

-SX ..... 850 nm

-LX ..... 1310 nm

Distance/Loss Budget

SX

-62/125u ..... 220 m

-Loss Budget ..... 7 dB

LX

-62/125u ..... 550 m

-Loss Budget ..... 10 dB

Connector ..... SC,ST

#### Power:

Voltage ..... 48 VDC

Current ..... 200 mA

Connector ..... 2 Pin Terminal Block

#### Recommended Power Supply:

48VDC @ 30W (Sold separately)

#### Environmental:

Temperature ..... -40 °C to +75 °C

Humidity ..... 5 % to 95 %

#### Size:

Module ..... 4¼" x 4¼" x 1½"



The American Fibertek 49-PoE Series transmits and receives (2) copper 10/100/1000 Base-T Ethernet signals at the RJ45 ports and (2) optical 1000 Base-X over 1 or 2 multimode fibers. The system is comprised of two or more units forming a communications link.

The 48SL-PoE Series also sources power to devices from the RJ45 ports over the copper connection. Both RJ45 ports may be used to deliver low power 802.3af (15 watts) to devices. A single RJ45 port is used to deliver high power 802.3at (30 watts) to a single device. An external power supply is required for the PoE module.

The system is designed to be completely transparent with auto negotiation features which automatically configures the unit for the correct speed (10/100/1000 Base-T).

Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

#### ORDERING INFORMATION:

MX-49-SX-SC-PoE	Two Fiber/Port, Module SX Multimode SC Connector
MX-49-LX-SC-PoE	Two Fiber/Port, Module LX Multimode SC Connector
MX-49-LX-1F-SC-PoE	One Fiber/Port, Module LX Multimode SC Connector
MX-49-SX-ST-PoE	Two Fiber/Port, Module SX Multimode ST Connector
MX-49-LX-ST-PoE	Two Fiber/Port, Module LX Multimode ST Connector
MX-49-LX-1F-ST-PoE	One Fiber/Port, Module LX Multimode ST Connector

#### POWER SUPPLY:

PS-48D	Universal Input to 48V 30W Output 0 to 50°C
PS-4830	Universal Input to 48V 30W Output -40 to 75°C

The PoE module is typically used only at the system edge (to power the camera etc.). The mating unit would then be the non PoE version of the product which is available in module or rack card packages.