

**(2) 10/100/1000Base-T & (2) 1000Base-ZX Ethernet
4 Port Switch / Drop & Repeat Transceiver with PoE+**
FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Drop and Repeat Capability
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100/1000 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Singlemode Fiber

SPECIFICATIONS:
Ethernet:

Data Rate
Auto negotiated..... 10/100/1000 Mb/s
Connector RJ45
PoE (2 RJ45 ports) 802.3af
PoE (2 RJ45 ports) 802.3at

Optical:

One Fiber..... 1490/1550 nm
Two Fiber.....1550nm
Distance
ZX 9/125u..... 70 km
Loss Budget24 dB
Connector.....SC/ST

Power:

Voltage..... 48 VDC
Current..... 200 mA
Connector 2 Pin Terminal Block

Recommended Power Supply:

48VDC @ 60W (Sold separately)

Environmental:

Temperature -40 °C to +75 °C
Humidity..... 5 % to 95 %

Size:

Module4¼" x 4¼" x 1⅛"



The American Fibertek 49ZX Series transmits and receives (2) copper 10/100/1000Base-T Ethernet signals at the RJ45 ports and (1) optical 1000 Base-ZX over 1 or 2 singlemode fibers up to a distance of 70 km. The system is comprised of two units forming a communications link.

The 49-ZX-PoE+ Series also sources power to devices from the RJ45 ports over the copper connection. Both RJ45 ports may be used to deliver low power 802.3af (15 watts) or 802.3at (30 watts) to PD powered devices. An external power supply is required.

The system is designed to be completely transparent with auto negotiation features which automatically configures the unit for the correct speed (10/100/1000 Base-T).

Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

ORDERING INFORMATION:

MX-49-ZX-SC-PoE+	Two Fiber/Port, Module ZX Singlemode SC Connector
MX-49-ZX-1F-SC-PoE+	One Fiber/Port, Module ZX Singlemode SC Connector
MX-49-ZX-ST-PoE+	Two Fiber/Port, Module ZX Singlemode ST Connector
MX-49-ZX-1F-ST-PoE+	One Fiber/Port, Module ZX Singlemode ST Connector

POWER SUPPLY:

PS-4860 Universal Input to 48V 60W Output -40 to 75°C

The PoE module is typically used only at the system edge (to power the camera etc.). The mating unit would then be the non PoE version of the product which is available in module or rack card packages.