



**50SL-PoE  
SERIES  
SINGLEMODE**

**(2) 10/100 Base-T & (2) 100Base-FX Ethernet 4 Port  
Switch / Drop & Repeat Transceiver with PoE**

**FEATURES:**

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Drop and Repeat Capability
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Multimode Fiber
- ◆ Power Over Ethernet on Both Ports

**SPECIFICATIONS:**

**Ethernet:**

Data Rate  
Auto negotiated ..... 10/100 Mb/s  
Connector ..... RJ45  
PoE (2 RJ45 ports) ..... 802.3af  
PoE (1 RJ45 port) ..... 802.3at

**Optical:**

One Fiber ..... 1310/1550 nm  
Two Fiber ..... 1310 nm  
Loss Budget ..... 20 dB  
Distance ..... 20 km  
Connector ..... SC, ST

**Power:**

Voltage ..... 48 VDC  
Current ..... 200 mA  
Connector ..... 2 Pin Terminal Block

**Recommended Power Supply:**

48VDC @ 30W (Sold separately)

**Environmental:**

Temperature ..... -40 °C to +75 °C  
Humidity ..... 5 % to 95 %

**Size:**

Module ..... 4¼" x 4¼" x 1⅛"



The American Fibertek 50SL-PoE Series transmits and receives (2) copper 10/100 Base-T Ethernet signals at the RJ45 ports and (2) optical 100 Base-FX over 1 or 2 multimode fibers. The system is comprised of two or more units forming a communications link.

The 50SL-PoE Series also sources power to devices from the RJ45 ports over the copper connection. Both RJ45 ports may be used to deliver low power 802.3af (15 watts) to devices. A single RJ45 port is used to deliver high power 802.3at (30 watts) to a single device. An external power supply is required for the PoE module.

The system is designed to be completely transparent with auto negotiation features which automatically configure the unit for the correct speed (10/100 Base-T). Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

**ORDERING INFORMATION:**

- |                       |  |
|-----------------------|--|
| MX-50-FX-SL-1F-SC-PoE | One Fiber/Port Module FX Singlemode SC Connector |
| MX-50-FX-SL-1F-ST-PoE | One Fiber/Port Module FX Singlemode ST Connector |
| MX-50-FX-SL-2F-SC-PoE | Two Fiber/Port Module FX Singlemode SC Connector |
| MX-50-FX-SL-2F-ST-PoE | Two Fiber/Port Module FX Singlemode ST Connector |

**POWER SUPPLY:**

- |         |   |
|---------|---|
| PS-48D  | Universal Input to 48V 30W Output 0 to 50°C   |
| PS-4830 | Universal Input to 48V 30W Output -40 to 75°C |

The PoE module is typically used at the edge (power the camera) location and the mating product would be the non PoE version of the product which is available in module or rack card.