



**50-SL-PoE-HP
SERIES
SINGLEMODE**

(2) 10/100 Base-T & (2) 100Base-FX Ethernet 4 Port Switch / Drop & Repeat Transceiver with 60W PoE

“Approved for AXIS Q6032-E PTZ Dome Network Camera”

FEATURES:

- ◆ Complete Fiber Optic to Twisted Pair Media Interface
- ◆ Drop and Repeat Capability
- ◆ Auto MDI / MDIX Detection
- ◆ Auto Negotiate 10/100 Ports
- ◆ Link and Activity Indicators for UTP and Fiber Ports
- ◆ Multimode Fiber
- ◆ Power (60 Watts) Over Ethernet on 1 Port
- ◆ Two RJ45 Data Ports Available
- ◆ Extended Temperature Range

SPECIFICATIONS:

Ethernet:

Data Rate

Auto negotiated.....10/100 Mb/s
Connector RJ45
PoE (1 port)60 Watts

Optical:

One Fiber 1310/1550 nm
Two Fiber 1310 nm
Loss Budget 20 dB
Distance20 km
Connector SC, ST

Power:

Voltage48 VDC
Current 200 mA
Connector 2 Pin Terminal Block

Recommended Power Supply:

48VDC @ 60W (Sold separately)

Environmental:

Temperature -40 °C to +75 °C
Humidity 5 % to 95 %

Size:

Module 4.3" x 4.3" x 1.2"
Power Supply 4.6" x 3.6" x 1.6"

10/23/12 JPM



The American Fibertek 46-PoE-HP Series transmits and receives (2) copper 10/100 Base-T Ethernet signals at the RJ45 ports and (1) optical 100 Base-FX over 1 or 2 multimode fibers. The system is comprised of two units forming a point-to-point communications link.

The 46-PoE-HP Series also sources up to 60 Watts of power to an Ethernet powered device (PD) from one RJ45 port. The power is carried over all 4 pairs of the Ethernet cable. However, it is required that the PD have independent discovery and classification interfaces for both the data pair and the spare pair of the Ethernet cable.

Both RJ45 ports may be used to deliver Ethernet data to devices. An external power supply is required.

The system is designed to be completely transparent with auto negotiation features which automatically configure the unit for the correct speed (10/100 Base-T). Auto MDI/MDIX operation eliminates the potential need for crossover cables. Diagnostic indicators provide a quick visual indication of system status.

ORDERING INFORMATION:

MX-50-FX-SL-1F-SC-PoE-HP One Fiber/Port Module FX Singlemode SC Connector
MX-50-FX-SL-1F-ST-PoE-HP One Fiber/Port Module FX Singlemode ST Connector
MX-50-FX-SL-SC-PoE-HP Two Fiber/Port Module FX Singlemode SC Connector
MX-50-FX-SL-ST-PoE-HP Two Fiber/Port Module FX Singlemode ST Connector

POWER SUPPLY:

PS-4860 Universal Input to 48V 60W Output -40 to 75°C

The PoE module is typically used at the edge (power the camera) location and the mating product would be the non PoE version of the product which is available in module or rack card.