

4.650

OLI OPTICAL
LOSS
INDICATOR

afi
american fibertek

**SINGLEMODE
FIBER OPTIC
TRANSCEIVER
MR-3485-2**

FIBER FC/PC

**DATA I/O +
DATA I/O -
GROUND
N.C.
N.C.**

**12 VAC
50 TO 60 Hz
20 VA MAX
Class 2
Wiring only**

VIDEO OUT

NOT
USED

8.400

OLI - OPTICAL LEVEL INDICATOR:
INDICATOR IS GREEN WHEN PROPER LEVEL IS PRESENT.
IT IS RED WHEN SIGNAL IS MISSING OR AT AN INCORRECT
LEVEL.

RS485 INPUT IS NOT INTERNALLY TERMINATED.
IF A TERMINATION IS REQUIRED, INSTALL A
120Ω 1/4 WATT RESISTOR ACROSS THE
DATA(+) AND DATA(-) CONNECTIONS ON
THE TERMINAL BLOCK

afi
american fibertek

120 BELMONT DRIVE SOMERSET N.J.

DATE: 28 AUG 07

ACAD FN.:
MR-3485-2 CC

SCALE: none
DWG BY: BLB

MR-3485-2
CUSTOMER ASSEMBLY DRAWING

DWG. NO.:
SH. OF
REV.:
CHK.: SK