

4.650

OLI OPTICAL
LOSS
INDICATOR

afi
american fibertek

**SINGLEMODE
FIBER OPTIC
TRANSCEIVER
MR-3486-4**

FIBER FC/PC

**DATA IN +
DATA IN -
GROUND
N.C.
N.C.**

**12 VAC
50 TO 60 Hz
20 VA MAX
Class 2
Wiring only**

VIDEO OUT

**DATA OUT +
DATA OUT -
GROUND
N.C.
N.C.**

8.400

OLI - OPTICAL LEVEL INDICATOR:
INDICATOR IS GREEN WHEN PROPER LEVEL IS PRESENT.
IT IS RED WHEN SIGNAL IS MISSING OR AT AN INCORRECT
LEVEL.

RS485 INPUT IS NOT INTERNALLY TERMINATED.
IF A TERMINATION IS REQUIRED, INSTALL A
120Ω 1/4 WATT RESISTOR ACROSS THE
DATA(+) AND DATA(-) CONNECTIONS ON
THE TERMINAL BLOCK

afi american fibertek 120 BELMONT DRIVE SOMERSET N.J.	DATE: 28 AUG 07		MR-3486-4			
	ACAD FN.: MR-3486-4 CC		CUSTOMER ASSEMBLY DRAWING			
	SCALE:	DWG BY: BLB	DWG. NO.:	SH. OF	REV.:	CHK.: <i>SK</i>