



LED INDICATORS:

UTP LINK/ACT: GREEN:1000 BASE-T
RED: 100 BASE-TX
AMBER: 10 BASE-T

BLINK: UTP LINK IS ESTABLISHED AND ACTIVITY IS ON UTP PORT.
SOLID: UTP LINK IS ESTABLISHED BUT NO ACTIVITY IS ON UTP PORT.
OFF: UTP LINK IS NOT ESTABLISHED.

FIBER LINK/ACT:1000 BASE-LX FIBER LINK AND ACTIVITY.

BLINK (GREEN): FIBER LINK IS ESTABLISHED AND ACTIVITY IS ON FIBER.
SOLID (GREEN): FIBER LINK IS ESTABLISHED BUT NO ACTIVITY IS ON FIBER.
OFF: FIBER LINK IS NOT ESTABLISHED.

OLI: RED: DC POWER IS ON BUT OPTICAL POWER IS MISSING OR AT INCORRECT LEVEL.
GREEN: DC POWER IS ON AND OPTICAL POWER IS AT PROPER LEVEL.

 afi american fibertek 120 BELMONT DRIVE SOMERSET N.J.	DATE: 03 MAR 2010		RRX-48-1610 CUSTOMER ASSEMBLY DRAWING		
	ACAD FN.: RRX-48-1610 CC				
	SCALE: NONE	DWG BY: CLQ	DWG. NO.:	SH. OF	REV.: