



CC1 TO CC8 – CONTACT CLOSURE INPUT INDICATORS:  
GREEN INDICATES THAT THE CONTACT INPUT CONNECTION IS CLOSED.

DC PWR – DC POWER:  
GREEN INDICATES THAT DC POWER IS ON.

RESET PUSH BUTTON:  
PRESSING THE MOMENTARY PUSH BUTTON CAUSES ALL THE CONTACT OUTPUTS AT THE MR/RR-81 UNITS TO TEMPORARILY SWITCH TO THEIR DEFAULT STATES (NORMALLY OPEN CONNECTIONS ARE OPEN; NORMALLY CLOSED CONNECTIONS ARE CLOSED). THIS IS USED PRIMARILY FOR TESTING PURPOSES.

CONTACT IN CH1 TO CH 8:  
THESE PROVIDE 8 CONTACT CLOSURE INPUT CONNECTIONS. CLOSING THE RESPECTIVE CONTACT CLOSURE INPUT CONNECTIONS CAUSES THE RESPECTIVE RELAYS IN THE MR/RR-81 TO SWITCH FROM THE DEFAULT STATE TO (NORMALLY OPEN CONNECTIONS ARE CLOSED) AND (NORMALLY CLOSED CONNECTIONS ARE OPEN).

 120 BELMONT DRIVE SOMERSET N.J.	DATE: 20 OCT 08		MT-81SL		
	ACAD FN.: MT-81SL CC		CUSTOMER ASSEMBLY DRAWING		
	SCALE: NONE	DWG BY: BLB/CLQ	DWG. NO.:	SH. 1 OF 1	REV.: