



CC1 TO CC16 – CONTACT CLOSURE INPUT INDICATORS:
GREEN INDICATES THAT THE CONTACT INPUT CONNECTION IS CLOSED.

DC PWR – DC POWER:
GREEN INDICATES THAT DC POWER IS ON.

RESET PUSH BUTTON:
PRESSING THE MOMENTARY PUSH BUTTON CAUSES ALL THE CONTACT OUTPUTS AT THE MR/RR-82 UNITS TO TEMPORARILY SWITCH TO THEIR DEFAULT STATES (NORMALLY OPEN CONNECTIONS ARE OPEN; NORMALLY CLOSED CONNECTIONS ARE CLOSED). THIS IS USED PRIMARILY FOR TESTING PURPOSES.

CONTACT IN CH1 TO CH 16:
THESE PROVIDE 16 CONTACT CLOSURE INPUT CONNECTIONS. CLOSING THE RESPECTIVE CONTACT CLOSURE INPUT CONNECTIONS CAUSES THE RESPECTIVE RELAYS IN THE MR/RR-82 TO SWITCH FROM THE DEFAULT STATE TO (NORMALLY OPEN CONNECTIONS ARE CLOSED) AND (NORMALLY CLOSED CONNECTIONS ARE OPEN).

 afi american fibertek 120 BELMONT DRIVE SOMERSET N.J.	DATE: 14 JULY 09		MT-82		
	ACAD FN.: MT-82 CC		CUSTOMER ASSEMBLY DRAWING		
	SCALE: NONE	DWG BY: BLB/CLQ	DWG. NO.:	SH. 1 OF 1	REV.: