



DATA 1 TX/RX INDICATORS:
GREEN WHEN DATA ACTIVITY
IS PRESENT. OFF WHEN NO
DATA ACTIVITY IS PRESENT.

DATA 2 TX/RX INDICATORS:
INDICATOR IS GREEN WHEN
CONTACT IS CLOSED.

VLI - VIDEO LEVEL INDICATORS:
OLI - OPTICAL LEVEL INDICATOR:
SYNC - SYNC INDICATOR:
INDICATORS ARE GREEN WHEN
PROPER SIGNALS/LEVELS ARE
PRESENT. THEY ARE RED WHEN
SIGNALS ARE MISSING OR AT
INCORRECT LEVELS.

RS485-4W IS THE FACTORY SHIPPED DATA CHANNEL
CONFIGURATION. THE CH. 1 DATA CHANNEL IS USER
CONFIGURABLE. SEE THE DATA SWITCH SETTINGS TABLE.

DATA SWITCH SETTINGS: ON IS DOWN								CHANNEL 1 DATA CONFIGURATION
1	2	3	4	5	6	7	8	
ON	ON	OFF	OFF	OFF	OFF	OFF	OFF	RS485-4W (FACTORY SHIPPED)
OFF	ON	ON	OFF	OFF	OFF	OFF	OFF	RS485-2W
ON	OFF	OFF	OFF	OFF	OFF	OFF	OFF	RS422
OFF	OFF	OFF	OFF	OFF	OFF	OFF	OFF	RS232

 120 BELMONT DRIVE SOMERSET N.J.	DATE:	08 MAY 07		MR-915 CUSTOMER ASSEMBLY DRAWING			
	ACAD FN.:	MR-915 CC					
	SCALE:	NONE	DWG BY:	BLB	DWG. NO.:	SH. OF	REV.: