SIDE VIEW



FRONT VIEW



PARTIAL SIDE VIEW



LINE CORDS
(PROVIDED WITH POWER SUPPLY)
PREPARE LINE CORD AND
CONNECT AS SHOWN

EURO CABLE

UK CABLE





DC CABLE
RECOMMENDED WIRE GAUGE:
18AWG STRANDED
(NOT PROVIDED WITH
POWER SUPPLY)



CONNECT TO 48Vdc
ON MODULE



TOP VIEW

92-06-0439 MOUNTING PLATE

PS-48V-60W POWER SUPPLY

POWER SUPPLY SPECIFICATIONS		
INPUT VOLTAGE RANGE	85-264	VAC
INPUT FREQUENCY RANGE	47-63	Hz
OUTPUT VOLTAGE	48	VDC
OUTPUT CURRENT RANGE	0-1.25	AMPS
OUTPUT POWER	60W @ 25C 30W @ 75C	WATTS
DC OK CONTACT OPENS WHEN OUTPUT DROPS BELOW 90%	30V / 1A	

afi
american fibertek
120 BELMONT DRIVE SOMERSET N.J.

DATE: 07 MAR 13		PS-4830-CE PoE POWER SUPPLY ASSY			
ACAD FN.: PS-4830-CE CC					
SCALE:	DWG BY: BLB	DWG. NO.:	SH. 1 OF 1	REV.:	CHK.: SK