



SFP – Small Form Pluggable Ethernet Modules

Model Number	Single/ Multimode/ Copper	Single/ Dual Fiber	Distance	Wavelength nm Tx/Rx	DataRate Mb/s	Tx Power dBm	Rx Sensi- tivity dBm	Rx Max In Pwr dBm	Loss Budget dB	Con- nector	DMI Yes/No	Compa- tibility	Case Temp °C
Copper 100/1000													
SFP-TX-100	Copper without LOS	Cat5	100m	NA	100	NA	NA	NA	NA	RJ45	No	MSA	-40 to +85
SFP-TX	Copper without LOS	Cat5	100m	NA	1000	NA	NA	NA	NA	RJ45	No	MSA	-40 to +85
Multimode 100/1000													
SFP-FX	Multi 62um	2	2km	1310/1310	100	-8to-15	-30	-3	15	LC	Yes	MSA	-40 to +85
SFP-FX- CISCO*3	Multi 62um	2	2km	1310/1310	100	-8to-15	-30	-3	15	LC	Yes	MSA	-40 to +85
SFP-SX	Multi 50um*1	2	550m	850/850	1000	-3to-10	-18	-3	8	LC	Yes	MSA	-40 to +85
SFP-SX- CISCO*3	Multi 50um*1	2	550m	850/850	1000	-3to-10	-18	-3	8	LC	Yes	MSA	-40 to +85
SFP-LX-2	Multi 50um*2	2	2km	1310/1310	1000	-3to-10	-22	-3	12	LC	Yes	MSA	-40 to +85
SFP-LX-2- CISCO*3	Multi 50um*2	2	2km	1310/1310	1000	-3to-10	-22	-3	12	LC	Yes	MSA	-40 to +85
SFP-FX1-2A	Multi 62um	1	2km	1310/1550	100	-8to-15	-34	-3	19	LC	Yes	MSA	-40 to +85

American Fibertek Inc. 120 Belmont Drive, Somerset, NJ, USA 08873-4342

Phone: 732.302.0660 Fax: 732.302.0667 Toll Free: 877.234.7200

Email: mail@americanfibertek.com

Model Number	Single/Multimode/Copper	Single/Dual Fiber	Distance	Wavelength nm Tx/Rx	DataRate Mb/s	Tx Power dBm	Rx Sensitivity dBm	Rx Max In Pwr dBm	Loss Budget dB	Connector	DMI Yes/No	Compatibility	Case Temp °C
SFP-FX1-2B	Multi 62um	1	2km	1550/1310	100	-8to-15	-34	-3	19	LC	Yes	MSA	-40 to +85
SFP-LX1-1A	Multi 62um	1	550m	1310/1550	1000	-3to-8	-22	-3	14	LC	Yes	MSA	-40 to +85
SFP-LX1-1B	Multi 62um	1	550m	1550/1310	1000	-3to-8	-22	-3	14	LC	Yes	MSA	-40 to +85
Singlemode 100/1000													
SFP-FX-15	Singlemode	2	15km	1310/1310	100	-8to-15	-34	-6	19	LC	Yes	MSA	-40 to +85
SFP-FX-15-CISCO*3	Singlemode	2	15km	1310/1310	100	-8to-15	-34	-6	19	LC	Yes	MSA	-40 to +85
SFP-LX	Singlemode	2	10km	1310/1310	1000	-3to-8	-22	-3	14	LC	Yes	MSA	-40 to +85
SFP-LX-CISCO*3	Singlemode	2	10km	1310/1310	1000	-3to-8	-22	-3	14	LC	Yes	MSA	-40 to +85
SFP-LX-40	Singlemode	2	40km	1310/1310	1000	0to-5	-25	-3	20	LC	Yes	MSA	-40 to +85
SFP-LX-40-CISCO*3	Singlemode	2	40km	1310/1310	1000	0to-5	-25	-3	20	LC	Yes	MSA	-40 to +85
SFP-ZX	Singlemode	2	80km	1550/1550	1000	0to5	-24	-3	24	LC	Yes	MSA	-40 to +85
SFP-FX1-20A	Singlemode	1	20km	1310/1550	100	-8to-15	-34	-6	19	LC	Yes	MSA	-40 to +85
SFP-FX1-20B	Singlemode	1	20km	1550/1310	100	-8to-15	-34	-6	19	LC	Yes	MSA	-40 to +85
SFP-LX1-20A	Singlemode	1	20km	1310/1550	1000	-3to-8	-22	-3	14	LC	Yes	MSA	-40 to +85
SFP-LX1-20B	Singlemode	1	20km	1550/1310	1000	-3to-8	-22	-3	14	LC	Yes	MSA	-40 to +85

American Fibertek Inc. 120 Belmont Drive, Somerset, NJ, USA 08873-4342
Phone: 732.302.0660 Fax: 732.302.0667 Toll Free: 877.234.7200
Email: mail@americanfibertek.com

Model Number	Single/Multimode/Copper	Single/Dual Fiber	Distance	Wavelength nm Tx/Rx	DataRate Mb/s	Tx Power dBm	Rx Sensitivity dBm	Rx Max In Pwr dBm	Loss Budget dB	Connector	DMI Yes/No	Compatibility	Case Temp °C
CWDM 1000													
SFP-1470-40	Singlemode	2	40km	1470	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1490-40	Singlemode	2	40km	1490	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1510-40	Singlemode	2	40km	1510	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1530-40	Singlemode	2	40km	1530	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1550-40	Singlemode	2	40km	1550	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1570-40	Singlemode	2	40km	1570	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1590-40	Singlemode	2	40km	1590	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1610-40	Singlemode	2	40km	1610	1000	-5 to 0	-25	-2	20	LC	Yes	MSA	-40 to +85
SFP-1470-80	Singlemode	2	80km	1470	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85
SFP-1490-80	Singlemode	2	80km	1490	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85
SFP-1510-80	Singlemode	2	80km	1510	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85
SFP-1530-80	Singlemode	2	80km	1530	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85
SFP-1550-80	Singlemode	2	80km	1550	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85
SFP-1570-80	Singlemode	2	80km	1570	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85
SFP-1590-80	Singlemode	2	80km	1590	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85

American Fibertek Inc. 120 Belmont Drive, Somerset, NJ, USA 08873-4342

Phone: 732.302.0660 Fax: 732.302.0667 Toll Free: 877.234.7200

Email: mail@americanfibertek.com

Model Number	Single/Multimode/Copper	Single/Dual Fiber	Distance	Wavelength nm Tx/Rx	DataRate Mb/s	Tx Power dBm	Rx Sensitivity dBm	Rx Max In Pwr dBm	Loss Budget dB	Connector	DMI Yes/No	Compatibility	Case Temp °C
SFP-1610-80	Singlemode	2	80km	1610	1000	0 to 5	-25	0	25	LC	Yes	MSA	-40 to +85
SFP-1470-120	Singlemode	2	120km	1470	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85
SFP-1490-120	Singlemode	2	120km	1490	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85
SFP-1510-120	Singlemode	2	120km	1510	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85
SFP-1530-120	Singlemode	2	120km	1530	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85
SFP-1550-120	Singlemode	2	120km	1550	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85
SFP-1570-120	Singlemode	2	120km	1570	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85
SFP-1590-120	Singlemode	2	120km	1590	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85
SFP-1610-120	Singlemode	2	120km	1610	1000	0 to 5	-32	-9	32	LC	Yes	MSA	-40 to +85

American Fibertek Inc. 120 Belmont Drive, Somerset, NJ, USA 08873-4342
Phone: 732.302.0660 Fax: 732.302.0667 Toll Free: 877.234.7200
Email: mail@americanfibertek.com

Model Number	Single/Multimode/Copper	Single/Dual Fiber	Distance	Wavelength nm Tx/Rx	DataRate Mb/s	Tx Power dBm	Rx Sensitivity dBm	Rx Max In Pwr dBm	Loss Budget dB	Connector	DMI Yes/No	Compatibility	Case Temp °C
Multimode 10G SFP+													
SFP+850-300	Multi 50um	2	300m	850	10G	-7 to -1	-10	-1	3	LC	Yes	MSA	-40 to +85
Singlemode 10G SFP+													
SFP+1310-10	Singlemode	2	10km	1310	10G	-8 to 0	-14	0.5	6	LC	Yes	MSA	-40 to +85
SFP+1310-40	Singlemode	2	40km	1310	10G	1 to 6	-13	0.5	14	LC	Yes	MSA	-40 to +85

*1 550m using OM2 50/125µm fiber, 220m using OM1 62.5/125µm fiber, (1000m using OM3 or OM4 50/125µm fiber)

*2 2Km using OM2 50/125µm fiber, 1Km using OM1 62.5/125µm fiber

*3 Cisco Compatible SFP. Call sales for Cisco compatible SFPs not on this table.

1_2019JPK

American Fibertek Inc. 120 Belmont Drive, Somerset, NJ, USA 08873-4342
Phone: 732.302.0660 Fax: 732.302.0667 Toll Free: 877.234.7200
Email: mail@americanfibertek.com